

Surveillance Cameras

5005-B and 5005-W

Channel Vision's water-proof bullet camera is versatile enough for most residential and commercial surveillance applications. This B&W camera measures slightly over 2 inches long and includes a universal 360° swivel mount and 3.6mm lens. The 5005 camera provides over 420 lines of resolution and works down to 0.05 lux making it the perfect choice for internal, external and covert surveillance.

Features:

- Over 420 Lines Of Resolution
- 0.05 Lux Sensitivity
- 3.6mm Lens Included
- Power Supply Included
- Universal Swivel Mount Included
- Miniature Size
- Versatile Design
- Water Proof
- Reverse Polarity Power Input Protection



Camera: 2-1/16" Long, 3/4" Diameter
Universal Mount: 1-5/8" High, 1-9/16" Deep

Specifications:

Image Pick-Up Device	1/3" CCD Area Sensor	Minimal Illumination	0.05LUX, f2.0
TV System	EIA, CCIR	S/N Ratio	More Than 48dB
No. of Pixels	EIA = 512(H) x 492(V) CCIR = 512(H) x 582(V)	Gamma Characteristic	0.45
Pixels Pitch	EIA = 9.6uM(H) x 7.5uM CCIR = 9.6uM(H) x 6.3uM	Video Output	1.0-1.1 VP-P 75Ω
Scanning System	EIA = 525 Lines, 60 Field/Sec. CCIR = 625 Lines, 50 Field/Sec.	Electronic Shutter Timer	EIA = 1/60-1/50,000 Sec. CCIR = 1/50-1/50,000 Sec.
Sync System	Internal Sync.	Lens Focal Length	Fixed 3.6mm (92°)
Resolution	420 Lines	Power Consumption	DC 8-12V / 100mA
Lens Diameter	19mm	Operating Temperature	-10° to +50° C RH 95% Max.
		Storage Temperature	-20° to +60° C RH 95% Max.



CHANNEL VISION™

234 FISCHER AVENUE • COSTA MESA, CA 92626

(714) 424-6500 • (800) 840-0288 • (714) 424-6510 fax

www.channelvision.com • email: sales@channelvision.com